



FLEXLOCK RUST REMOVER FOR CONCRETE PAVERS, WETCAST & NATURAL STONES

TDS Revision Date (dd/mm/yyyy): 21/06/2019

TECHNICAL DATA SHEET

- Update:** June 21, 2019
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **FLEXLOCK RUST REMOVER** is effective in removing rust from the surface of concrete pavers, wetcast & natural stones.
- Features:**
- Removes the spots caused by steel, water build up, fertilizer, etc.
 - Washes off with water.
 - Contains no muriatic acid.
- For use on:** Concrete pavers, wetcast & natural stones.
- Please note:**
1. Do not let product dry up on paver surface.
 2. Wear goggles and rubber gloves.
 3. After using the **FLEXLOCK RUST REMOVER** on various spots, clean the entire paver surface with Flexlock Efflorescence Cleaner for an overall uniform color.

Application instructions:

1. Apply product on stain.
2. Let it soak for 2-3 minutes.
3. Scrub with a hard bristle brush.
4. Rinse thoroughly with water.
5. Repeat step 1 to 4 until the stain dissolves.

Packaging:	Product	Size	per Box	per Pallet
	FLEXLOCK RUST REMOVER	946 ml (1 QT.)	6 units	24 boxes

LIMITED WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose.

*Please store container at above 32°F / 0°C.



FLEXLOCK RUST REMOVER
FOR CONCRETE PAVERS, WETCAST & NATURAL STONES
TDS Revision Date (dd/mm/yyyy): 21/06/2019

DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. CAUSES BURNS. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Wear a mask, impervious gloves and safety glasses. Use only in a well-ventilated area. Handle with care.

FIRST AID TREATMENT:

Contains Potassium hydroxide, Silicic acid, sodium salt and Polyphosphoric acids. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

